



ATTORNEY DOCKET No. : 4530.01500
CLIENT DOCKET No. : PALM INC. 3545

5 **GENERIC ACTIVATION AND REGISTRATION FRAMEWORK FOR WIRELESS
DEVICES**

Inventor:
Brian Gerald Kuhn

10

COPYRIGHT NOTICE

15

A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyright rights whatsoever.

20

CROSS REFERENCE TO RELATED APPLICATION

25

This application is related to U.S. Patent Application Serial Number ____/____,____ filed on the same date as the present application entitled "USER INTERFACE TECHNIQUE FOR SELECTION AND ACTIVATION OF WIRELESS SERVICES FROM AMONG MULTIPLE TRANSPORT CARRIERS", by inventors Craig Skinner, William Shu-woon Wong, and Brian G. Kuhn, the entire disclosure of which is hereby incorporated by reference as if fully set forth herein.

30



BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention generally relates to wireless networks and, more particularly, to wireless network activation with carriers and registration with service providers.

10 Discussion of Background

15 The wireless communication revolution is bringing fundamental changes to data networking and telecommunication, and is making integrated networks a reality. By freeing the user from the cord, personal communications networks, wireless local area networks (LAN's), and mobile radio networks and cellular systems harbor the promise of fully distributed mobile computing and communications, any time, anywhere. Numerous wireless services are also maturing and are poised to change the way and scope of communication.

20 Many manufacturers have begun to incorporate wireless technologies into a new kind of computer--the personal digital assistant (PDA). A PDA is a computer that is small enough to be held in the hand of a user. A PDA runs personal information management applications such as an address book, a
25 daily organizer, and electronic notepads. These applications make people's lives easier.

FIG. 1 shows a basic configuration of a popular PDA brand, the Palm™ 10. However, the Palm™ 10 is much more than a simple PDA. This small, slim, device, about the size of your wallet, can hold 6000 addresses, 5 years of appointments, 1500 to-do items, 1500 memos, 200 e-mail messages, and can run many different software applications.

The front panel of the Palm™ 10 is a large liquid crystal display ("LCD") 11, which is touch-sensitive and allows a user to enter and manipulate data. By using a stylus (not shown) to interact with the touch-sensitive screen, a user may easily navigate through a host of various software applications. A stylus is used to interact with information on a screen in much the same way a mouse is used with a desktop personal computer. The display device also includes a Graffiti™ writing section 12 for tracing alphanumeric characters as input.

Regarding wireless connectivity, a given wireless network typically has many different carriers for the same network type. For example, Bell South™ and Rogers AT&T™ are wireless carriers that both run Mobitex™ networks. Further, many wireless computers are manufactured to be compatible with a particular network type, carrier, and/or service provider.

Unfortunately, problems arise when a consumer, manufacturer, or provider later desires the computer to be compatible with another network or another carrier. Integrated within the computer's architecture, may be an

operating system that allows a user to connect with a specific carrier and/or service provider. For example, applications that allow connectivity with a specific carrier, such as BellSouth™, may be written to a read-only memory (ROM) of the PDA. Such a framework makes it difficult to later make the PDA compatible with another carrier or with another type of network.

The PDA that is compatible with only BellSouth™ can not be taken to Europe to be compatible with a French carrier, much less a wireless network in France. Thus, the manufacturer that builds the PDA that is compatible with BellSouth™ will have to build a different PDA to be compatible with a French carrier, and another device for Australia, and another for Japan, etc.

While a PDA may be manufactured for a regional carrier and/or service provider, wireless networks naturally provide users with extended computing capabilities and mobility. Users are able to move about, carrying their computers with them and maintaining uninterrupted communication with their servers. Wireless networks should be able to allow users to turn on their computers almost anywhere in the world, to establish access to their home servers, and to retrieve their files and email. Such mobility, however, is difficult with commonly available wireless technology.

Consequently, the implementation of wireless networks presents new problems. Unfortunately, classical communication

SUMMARY OF THE INVENTION

It has been recognized that what is needed is a framework for providing broader compatibility with wireless networks. Broadly speaking, the present invention fills these needs by providing a system and method for managing wireless network activation with a carrier and for handling registration with a service provider. It should be appreciated that the present invention can be implemented in numerous ways, including as a process, an apparatus, a system, a device or a method. Several inventive embodiments of the present invention are described below.

In one embodiment, a method is provided for managing network activation with a carrier and registration with a service provider. The method comprises: determining a network activation status with a carrier; if not activated, performing network activation procedures; determining a registration status with a service provider; if not registered, sending a request to a server of the service provider for a registration file configured to gather user registration information; receiving the registration file from the server; and executing the registration file.

In another embodiment, a generic framework is provided for network activation and registration. The framework comprises: a generic driver device configured to manage network activation procedures and registration procedures; and

a plug-in device configured to initiate registration procedures based on commands received from the driver, wherein the plug-in device is tailored to a particular service provider.

5 In still another embodiment, the framework is provided wherein the plug-in device includes an address to a registration file configured to gather user registration information for the particular service provider.

Advantageously, the present invention provides a generic
10 framework for activation and registration. The generic framework can be configured to be compatible with multiple carriers and/or service providers for any language. The generic framework can also be used for multiple wireless network types. No longer does a personal computer have to be
15 manufactured to be compatible with individual carriers, particular service providers, or specific networks. Easily installable plug-in devices can be tailored to each carrier, service provider, or network type. Accordingly, carriers can readily make themselves compatible with a given personal
20 computer without having to change the personal computer's ROM to fit the particular carrier, service provider, or network type. Thus, a generalized infrastructure is put in place to bring new carriers and personal computers online substantially quicker.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be readily understood by the following detailed description in conjunction with the accompanying drawings. To facilitate this description, like
5 reference numerals designate like structural elements.

FIG. 1 shows a basic configuration of a popular PDA brand, the Palm™.

FIG. 2 is a block diagram of selected components of a computer that includes wireless network technology, in
10 accordance with one embodiment of the present invention.

FIG. 3 is a block diagram of the architecture for the generic activation and registration framework (GARF), in accordance with one embodiment of the present invention.

FIG. 4 shows a high-level flowchart for a method of
15 managing network activation with a carrier and registration with a service provider, in accordance with one embodiment of the present invention.

FIG. 5A shows a more detailed flowchart for a method of
20 managing network activation with a carrier and registration with a service provider, in accordance with one embodiment of the present invention.

FIG. 5B is a continuation of the flowchart of FIG. 5A, in accordance with one embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

An invention is disclosed for a system and method for managing network activation with a carrier and registration with a service provider. Numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be understood, however, to one skilled in the art, that the present invention may be practiced without some or all of these specific details.

10 General Overview

FIG. 2 is a block diagram of selected components of a computer 100 that includes wireless network technology, in accordance with one embodiment of the present invention. The computer 100 includes a processing device 110, for executing applications and an operating system of the computer 100, a memory device 120 for storing the operating system, data, and applications (including plug-in executable files).

A display screen 130 is provided (preferably a touch sensitive screen) for display of operating system prompts, buttons, icons, application screens, and other data, and for providing user inputs via tapping or touching (or drawing in the Graffiti™ area) via a stylus or other touch mechanism. Hardware interface 135 connects to physical hard buttons and switches located on a body of the computer 100 and provides signals to applications running on the processing unit 110.

A bus 155 carries data and commands to/from the processing unit 110 from/to other devices within the computer 100. For example, user applications running on the computer 100 may be stored in the memory device 120. The user applications send application screens and other data outputs to display screen 130 for display via the bus 155. User inputs (Graffiti™ area drawing, or tap selection, for example) are detected by the screen 130 and sent to the processing unit 110 via the bus 155.

A mobile radio device 140 (part of the wireless technology in the computer 100) provides connectivity to a wireless network (not shown). The mobile radio device 140 is configured to detect inbound network transactions from the network directed toward the mobile radio device 140. For example, the inbound network transaction may be a page notification that is sent to a pager device executing on the processing unit 110.

In the embodiment of FIG. 2, the computer 100 is illustrated as a personal digital assistant (PDA). A PDA is a handheld computer such as a Palm™, Palm III™, or Palm V™, or Palm VII™ organizers, manufactured by Palm, Inc. Other embodiments of the invention can include Windows CE™ and Visor™ handheld computers, other handheld computers, other personal digital assistants (PDAs), desktop computers, laptop computers, workstations, or mainframes.

The Palm™ its operating environment are used herein to illustrate various aspects of the present invention. However, it should be understood that the present invention may be practiced on other devices, including other Palm™ models, PDA's, computer devices, personal computers, notebooks, etc.

General Overview Of Generic Activation And Registration Framework

FIG. 3 is a block diagram of the architecture for the generic activation and registration framework (the "GARF") 200, in accordance with one embodiment of the present invention. The GARF is a system for providing network activation and registration in a network that may have multiple carriers and/or service providers.

The GARF 200 provides a driver device 202 that generally controls network activation and registration procedures for the computer 100. Networking applications that may be tailored for a specific carrier or service provider are not included in the driver device. Rather, a plug-in device 204 (or multiple plug-in devices) may be installed in the computer 100. A plug-in device 204 includes hardware and/or software specifically tailored for a particular carrier and service provider. Through a given plug-in device 204, the computer

100 can communicate with a carrier and service provider that is intended for that plug-in device 204. For example, a driver device 202 may communicate with a provider's web server 206 with assistance from the plug-in device 204.

5 Additionally, the provider's web server 206 can send a registration file 208 to the driver device 202, which can then launch the registration file 208 in the computer 100. The registration file 208 is an executable file configured to allow the computer 100 to be compatible with a particular
10 carrier and/or service provider.

The GARF 200 allows manufacturers to build a computer 100 for operation in wireless networks of any verbal language. For example, a generic driver device 202 may be built that is nonspecific to any particular verbal language. The plug-in
15 device 204, on the other hand, may be then be configured to be language specific. If France, for instance, has three different service providers that operate the same way in the French language, the GARF 200 allows one computer 100 to communicate with all three service providers. In another
20 embodiment, the plug-in device 204 is generically built such that the computer 100 is generically operable in any wireless network of any verbal language.

Overview of Driver Device

The driver device 202 is hardware, software, or combination thereof, that is configured to manage procedures of the GARF 200. In one embodiment, the driver device 202 includes an icon on the display screen 130 for a user to select. Selection of the icon launches GARF 200 procedures, including activating a wireless network with a carrier and handling user registration with a service provider. BellSouth™, used with Palm VII™, is an example of a carrier. Palm.Net™, used with Palm VII™, is an example of a service provider. Palm.Net™ currently resells BellSouth™ services for use with Palm VII™.

In one embodiment, the driver device 202 is an executable application that a user will launch upon their first interaction with a wireless capable computer 100. The driver device 202 will drive the configuration of the computer 100 to obtain wireless connectivity, as well as perform the tasks required to obtain an account and/or identity with a particular carrier and/or service provider. In one example, the driver device 202 may be launched by applications such as Clipper™ (used in the Palm™ operating system) when wireless connectivity has not yet been established for the computer 100.

A feature of the GARF 200 is the ability for a user to step through a number of screens in order to provide personal

data to a wireless service provider, such as Palm.Net™. This setup process involves a number of steps, including retrieving the appropriate screen(s), entering user information, submitting the information to the driver device, writing the personal data in memory, and submitting the data to the service provider.

The driver device 202 is responsible for maintaining the system features (via the plug-in device 204). As an example, the Palm™ operating system requires certain system maintenance to ensure successful network transactions with the carrier and service provider. The driver device 202 accomplishes its tasks by launching a plug-in device 204 to activate the network on the device (and to display location/carrier-specific user interfaces and error messages). The driver device 202 can also call upon a registration file 208, which in turn may be configured to execute registration procedures on the computer 100. The driver device 202 exposes and calls upon application program interfaces (API's) in both the plug-in device and the registration file 208.

The driver device 202 is not tailored to a specific carrier and/or service provider. Rather, the driver device 202 is generic to various carriers and/or service providers in a given wireless network. For example, the driver device 202 may be generally operable in all networks in France, but the internal components are not programmed to handle

communications with one specific carrier and/or service provider. In one embodiment, the driver device 202 is built into the memory device 120 or, more specifically, into a read-only memory (ROM) portion of the memory device 120.

5 In one embodiment, communications from the provider's web server 206 to the driver device 202 are handled in a protocol that includes Hypertext Transfer Protocol (HTTP) over Transmission Control Protocol/Internet Protocol (TCP/IP). Communications from the driver device 202 to the carrier are
10 handled in a protocol that includes Hypertext Transfer Protocol (HTTP) over Compressed Transfer Protocol (CTP), or the carrier's own network protocol is used. Another embodiment handles communications with File Transfer Protocol (FTP) over TCP/IP. Other types of TCP/IP-based protocols may
15 alternatively be used to communicate. The present invention is not limited to the specific protocols disclosed herein.

In an alternative embodiment, deactivation of the carrier and de-registration of the service provider can occur. A computer 100 is deactivated when the computer 100 is no longer
20 enabled to communicate in the wireless network. A computer 100 is de-registered when the computer 100 no longer has an account with a service provider. Deactivation or de-registration can occur in at least the following two ways: some external process (outside of the computer 100) can be
25 invoked to execute deactivation or de-registration; or the

plug-in device 204 can be explicitly prompted to execute deactivation or de-registration.

To deactivate/de-register a computer 100, the driver device 202 searches through all plug-in devices 204 in the computer 100. If no plug-in devices 204 are found, deactivation is complete because without a plug-in device, a computer 100 is not network activated. In searching for plug-in devices 204, the computer 100 determines which network plug-in device is responsible for deactivation. The driver device 202 launches the found plug-in with a deactivation code. Note that the deactivation code must be accompanied by appropriate parameters to denote the desired plug-in device for deactivation. If the plug-in device also contains the service provider's registration (or de-registration) set of codes, the driver device 202 must determine whether to launch the plug-in device 204 with a "de-register" code first. In one embodiment, the deactivation code is called by a registration file 208 that is in the process of deactivating a component of service.

Overview of Plug-in Device

The plug-in device 204 is hardware, software, or combination thereof, that allows the computer 100 to be compatible with a particular carrier and particular service provider. In a preferred embodiment, the plug-in device 204

is an interface between software (e.g., wireless browser application) and hardware (e.g., mobile radio device 140) in the computer 100.

The plug-in device 204 may be configured to assist in establishing activation and registration, by executing functions such as the following: setting system features for the network activation upon resetting of the GARF 200; network activation/deactivation with a particular carrier and registration/de-registration with a particular service provider; maintenance of account identification for a particular carrier and a particular service provider; and initiating appropriate user interfaces during error conditions.

In a preferred embodiment, the plug-in device has the following two primary purposes upon launch by the driver device 202: (1) activate the computer 100 on a wireless network; and (2) register the computer 100 with a service provider such as Palm.Net™, thereby allowing the computer 100 to utilize the service provider's wireless services. The purpose of the GARF 200 is to perform common procedures in the wireless network. The plug-in device 204 is the component of the GARF 200 that contains differences for a particular mobile radio device 140, a particular carrier, and a particular service provider, among other things. In one embodiment, the

plug-in device 4 is an executable file that is easily installable into memory of the computer 100.

A plug-in device 204 is responsible for network activation and registration, setting system features, and updating the memory state of the computer 100 according to the network being activate. In one embodiment, the plug-in device 204 is tailored for a particular carrier and particular service provider. BellSouth™ is an example of a carrier. Palm.net™ is an example of a service provider. The carrier and service provider, in turn, operate in a particular type of network. Mobitex™ is an example of a wireless packet data network. Other examples of a network include a cell phone network, a digital personal communications service (PCS) network, and a global system for mobile communications (GSM) network. Thus, the plug-in is further configured to be compatible with the network in which the particular carrier operates.

As a secondary function, the plug-in device 204 provides error and warning code user interfaces, which are tailored to a particular verbal language (e.g., French, English, German, Spanish).

In another embodiment, the plug-in device 204 is designed to be compatible with multiple carriers and service providers in a given network. For example, the plug-in device 204 may be multiplexed to receive a call from the driver device 202,

and the plug-in device 204 may then switch between different carriers, depending on the call. In still another embodiment, multiple, different plug-in devices 204 may be installed in the computer 100, for example, to allow the user to have a choice of various carriers and/or service providers. In yet another embodiment, a general plug-in device 204 is provided, for example, a plug-in device compatible with an English language wireless network covering all of North America. Alternatively, a more specific plug-in device 204 may be installed to handle carriers and service providers, for example, in just the western United States.

Further, the different plug-in devices 204 may be configured to be compatible with each other. Regardless of the particular configuration of the plug-in devices 204, however, a plug-in device 204 is a component that can be readily redesigned after a computer 100 has been manufactured. Such flexibility of a plug-in device 204 is useful because hardware and software components in a computer 100 may be entrenched within the computer's operating system (e.g., the ROM). Thus, the plug-in device 204 provides a component for the computer 100 that facilitates changing the computer's compatibility for different carriers and/or service providers.

Regarding commands that the driver device 202 sends to the plug-in device 204, a plug-in device 204 is preferably designed to handle certain predefined launch codes from the

driver device 2 Table 1 below contains samples of launch codes that may be used in the Palm™ operating system.

21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

PLUGIN_TYPE	Return a wireless network or service provider, or both to the caller—noting the type of plug-in
WN_RESET	Set any system features needed for network stack of device release
SP_RESET	Set any system features needed for service provider
CK_WN_ACTIVATE	Check system feature and memory values (when system features may not be correct) to determine (true or false) if the wireless network is active
WN_ACTIVATE	Configure a device so that it is able to effectively communicate on the network
WN_DEACTIVATE	Perform a wireless network deactivation
CK_SP_REGISTER	Check system features and database entries (when system features may not be correct) to determine (true or false) if the service provider has been registered with. If the service provider has not been successfully registered with, this call will return false, with an optional parameter of a URL. The URL can then be used by the driver to retrieve a registration file 208.
SP_DEACTIVATE	Remove any system features, database entries, or flash values utilized by the service provider to denote successful registration.
SP_COMPLETE	Perform any service-provider-centric flash/system feature/database entry activity that denotes the FINAL step of activation and registration
SP_FAIL	Perform any service-provider-specific cleanup activity that must be performed to return the state of the device to normal

Table 1. Examples Of Launch Codes That Driver Device 202 May Include In A Command Sent To Plug-In Device 204

Overview of Auxiliary Screen Flow

In order to create and provision accounts with a given service provider, the service provider most-likely wants to collect data about the user. Such data may include name,
5 address, account identifier, password, etc.

The auxiliary screen flow of the GARF 200 involves downloading and executing a registration file 208 from the provider's web server 206. A registration file 208 is preferably an executable file configured to be executed as-is
10 on the computer 100. (In the Palm™ operating system, an executable file is commonly referred to as a "PRC".) The registration file 208 renders a set of dialogs (or "screens") to collect user registration data. The registration file has a calling convention and an expected set of results. The
15 driver device 202 can then control procedures to set up the account for the user.

In other words, in order to collect user information for service provider registration, the driver device 202 has the ability to dynamically query (i.e., download) a server of the
20 provider for the registration file 208. The registration file 208 is preferably kept as minimal in size as possible so as not to unduly delay the user's experience. As an example, the plug-in device sends a uniform resource locator (URL), or address, to the driver device 202. The driver device 202 in
25 turn sends a request to the provider's web server 206 to

retrieve the registration file 208 located at the URL. Once retrieved, the registration file 208 may be executed on the computer 100 to collect user registration data. In one embodiment, execution of the registration file 208 involves communicating directly with the web, without first going through the driver device 202.

The registration file 208 should be a temporary executable file configured to delete itself after its operations have been performed (i.e., after registration is complete). The registration file 208 should exit execution successfully (or with a failure error) directly to the driver device 202, so that any cleaning-up or processing by the computer 100 may resume. In other words, the registration file 208 should not leave the computer 100 in an unstable state. In one embodiment, the registration file 208 uses Compressed Transfer Protocol (CTP) calls. The registration file 208 may be configured to utilize error and warning user interfaces contained within the plug-in device 204. In a preferred embodiment, the registration file 208 is configured to utilize error and warning user interfaces contained within the registration file 208 itself.

The registration file 208 can be configured dynamically by the service provider. For example, if the service provider changes its rate plan, the registration file 208 can readily be changed to accommodate the new rate plan. The new rate

plan can then be displayed to the user when the registration file 208 is downloaded and executed on the computer 100. Note that the registration file 208 resides outside of computer 100 (at provider's web server 206, for example) before the registration file 208 is downloaded and executed by the driver device 202.

Overview of Provider's Web Server

In a preferred embodiment, the provider's web server 206 is accessible via a communication network. Examples of a communication network include a local area network (LAN), a wide area network (WAN), the global packet-switched network known as the "Internet" or the "World Wide Web" (web). The web server 206 provides the registration files 208 of the auxiliary screen flow, as well as any other logic to be used from within the executable file. In one example, the provider's web server 206 is accessible via the Internet through Palm™ Web Clipping Proxy Servers. HTTP is the proxiable protocol handled by Web Clipping Proxy Servers.

As discussed above with reference to the auxiliary screen flow, the plug-in device 204 may return a URL to the driver device 202. The URL is then sent as a request to the provider's web server 206. That URL returns one static registration file 208 for the auxiliary screen flow. Accordingly, the service provider preferably carves some space

from its file system directory to store the screens for the execution of the registration file 208.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241

FIG. 4 shows a high-level flowchart for a method of managing network activation with a carrier and registration with a service provider, in accordance with one embodiment of the present invention. The method starts in step 301 where a network activation status is determined. It may be determined, for example, that a wireless network for the mobile radio device 140 is enabled, but the computer 100 is not activated with a carrier. In such a case, the computer 100 will perform network activation procedures in step 302.

In step 303, registration status with a service provider is determined. If the computer 100 is not registered, a request will be sent to a server of a service provider in step 304. This request preferably contains an address to a registration file 208 configured to gather user registration information. The registration file is received from the server in step 306. In step 308, the registration file 208 is executed on the computer 100. Execution of the registration file 208 involves gathering registration information from the user. In another embodiment, the method further includes returning the gathered data to the server to complete network activation.

In one embodiment, the method steps of FIG. 4 are managed by the driver device 202. As discussed above with reference to FIG. 3, the driver device will drive the configuration

process to obtain wireless network activation, as well as perform the tasks required to obtain an account and/or identity with a particular service provider.

FIG. 5A and FIG. 5B, collectively, show a more detailed flowchart for a method of managing network activation with a carrier and registration with a service provider, in accordance with one embodiment of the present invention. The method starts in step 402 where a driver device 202 in the computer 100 is launched. For example, the driver device 202 may include a user-selectable icon on the display screen 130 of the computer 100, as discussed above with reference to FIG. 3. Upon selection of the icon, the driver device 202 is launched, thereby starting procedures of the GARF 200.

In step 404, the plug-in device 204 is launched to check for network activation with a carrier. As discussed above with reference to FIG. 3, the computer 100 may contain multiple, different plug-in devices 204. In a preferred embodiment, the driver device 202 scans for all of the plug-in devices 204 by searching the computer 100 for devices that match a particular file type. Accordingly, when a plug-in device 204 is designed, the plug-in device 204 should be designed to match a predetermined type that is searchable by the driver device 202. In one embodiment, the driver device 202 makes a call to each and every plug-in device 204 and checks for network activation in each.

As an example of step 404, the driver device 202 sends a "check wireless network activation" command (e.g., CK_WN_ACTIVATE) to a plug-in device 204 that has information on whether the computer 100 is network activated. "Network activated" means that the computer is capable of communicating in the network (e.g., Mobitex™) provided by the carrier (e.g., BellSouth™). Accordingly, a given wireless network can have multiple, different carriers operating in the given wireless network type. In a preferred embodiment, the computer 100 is manufactured to be network activated by having the mobile radio device 140 and appropriate network components built into the operating system of the computer 100. If the computer 100 is not network activated, a plug-in device 204 is launched in step 405 to activate the network with the computer 100. The launched plug-in device handles the activation process. If network activation fails, an error is returned to the driver device 202, an appropriate error message is displayed, and the method is done.

Assuming the computer 100 is appropriately network activated, a plug-in device 204 is launched to check for registration with a service provider in step 406. "Device" registration means that the computer 100 has an account with a service provider in the wireless network. In an alternative embodiment, "user" registration means that the user of the computer 100 has an account with the service provider. In

another embodiment, both the device and the user may be registered with the service provider, and the account with the service provider contains information specific to both the user and the particular device (i.e., computer 100). In this description, "device" registration and "user" registration may be used interchangeably to refer generally to account registration with a service provider.

In decision operation 408, it is determined if the device is registered with a service provider. In other words, it is determined if an account exists with a service provider in the given wireless network. If the device is registered, a plug-in device is launched in step 410 with an error to indicate the device is already registered. For example, a dialog screen (e.g., "Already Activated") is displayed to indicate to the user that the computer 100 has previously been registered with Palm.Net™.

However, if the device is not registered, an address to a registration file 208 is received from the plug-in device 204 in step 412. For example, the plug-in device 204 may have a URL for a registration file 208, as discussed above with reference to FIG. 3. In one embodiment, this registration file 208 is located on a provider's web server 206. The registration file 208 is an executable file configured to gather registration information from the user. The plug-in device 204 sends the registration file's URL to the driver

device 202 upon determining that the computer 100 is not registered with the particular service provider.

In step 414, a request is sent to a server of the service provider for the registration file 208. For example, as discussed above with reference to FIG. 3, the driver device 202 sends an HTTP request to a web server of the service provider. The HTTP request includes the registration file's URL. Communications with the provider's web server 206 may include procedures for encrypting data, connecting with the web server, and sending the URL to the web server. Information that may be imbedded in the URL includes the following: carrier identification, the type of verbal language (e.g., English or French) in which the computer 100 is operating, screen resolution of the display screen 130, and other environmental information of the computer 100.

In step 416, the registration file 208 is received from the server. For example, upon receiving the HTTP request from the driver device 202, the web server directs the registration file 208 to be returned to the computer 100.

The method continues in FIG. 5B with launching the registration file 208 in step 418. For example, as discussed above with reference to FIG. 3, an auxiliary screen flow is downloaded from the web and is executed on the computer 100. Launching the registration file starts in decision operation 420, where it is determined if an account is to be setup with

the particular service provider. For example, the registration file 208 displays a dialog on the display screen 130 to query the user if an account is to be setup. If an account is not to be setup, a "Cancel" screen is displayed in step 422 and the method is done. For example, the user may select a "Cancel" icon that initiates cancellation procedures of the registration process.

If an account is to be setup, registration information is then received from the user in step 424. For example, dialog screens are displayed during execution of the registration file 208 for the user to respond to registration queries. These dialog screens may query the user for some of the following information: username, alternative username, password, password question, password answer, first name, last name, email address, gender, birthday, and mailing address. The computer 100 receives the corresponding user-inputted information.

After user registration is received, it is determined in decision operation 426 if registration is to be confirmed or cancelled. For example, a dialog screen appears to query the user of whether to "confirm" or to "cancel" the registration process with the service provider. If registration is to be cancelled, the registration process is ceased and control is returned to the driver device 202 in step 440.

However, if registration is to be confirmed, the data gathered by the registration file 208 in step 424 is returned

to the provider's web server 206 to complete network registration in step 428. For example, the registration file 208 sends the gathered account data to the driver device 202, which in turn sends the gathered account data to the provider's web server 206.

In decision operation 430, it is determined if registration is acceptable to the service provider. For example, upon receiving the account data, the service provider responds in approval or denial of registration. Registration may be unacceptable for the following reasons: insufficient information (e.g., no username provided by the user), or invalid information (e.g., a password that is too short or a username that is already in existence). If registration is not acceptable, an "Error" screen is displayed in step 436. The user will be queried whether to retry. If the user does not want to retry registration, control is returned to the driver device 202 in step 440. However, if the user does want to retry, the method returns to step 418 where the registration file 208 is reset and launched.

On the other hand, if registration is acceptable, a "Done" screen is displayed in step 432. For example, the registration file 208 launches the done screen to indicate to the user that registration is acceptable and confirmed with the service provider. In step 434, a user identification is received from the provider's web server 206. For example, the

web server returns an identification code that uniquely identifies the computer 100 and/or the user for future logons with the service provider.

In one example, the identification code is accompanied by an HTTP cookie for the computer 100 to store in a cookie jar in the computer 100. An HTTP cookie, in this context, is a text file that contains registration information necessary for logons with the service provider. A cookie jar is a memory location in the computer 100 for storing HTTP cookies. The HTTP cookie may be retrieved from the cookie jar during future logons. The HTTP cookie will allow for quick and easy logons, that is, when the user logs onto the same service provider using the same computer 100.

If for some reason the user identification is not properly received from the provider's web server 206, error messages are displayed and the computer 100 retries to get the user identification from the provider's web server 206.

In step 440, control of network setup procedures is returned to the driver device 202. Success or failure parameters from the registration process are also returned to the driver device 202. Registration completion operations are then performed in step 442. For example, the driver device 202 may send success commands to a plug-in device 204, which will in turn initiate displaying of successful completion screens. Alternatively, the driver device 202 may send failure commands to a plug-in device 204, which will in turn

initiate displaying of cancellation screens. Upon performing the completion operations, the method is then done.

System And Method Implementation

5 Portions of the present invention may be conveniently implemented using a conventional general purpose or a specialized digital computer or microprocessor programmed according to the teachings of the present disclosure, as will be apparent to those skilled in the computer art.

10 Appropriate software coding can readily be prepared by skilled programmers based on the teachings of the present disclosure, as will be apparent to those skilled in the software art. The invention may also be implemented by the preparation of application specific integrated circuits or by
15 interconnecting an appropriate network of conventional component circuits, as will be readily apparent to those skilled in the art.

20 The present invention includes a computer program product which is a storage medium (media) having instructions stored thereon/in which can be used to control, or cause, a computer to perform any of the processes of the present invention. The storage medium can include, but is not limited to, any type of disk including floppy disks, mini disks (MD's), optical discs, DVD, CD-ROMs, micro-drive, and magneto-optical disks, ROMs,
25 RAMs, EPROMs, EEPROMs, DRAMs, VRAMs, flash memory devices (including flash cards), magnetic or optical cards,

nanosystems (including molecular memory), RAID devices, remote data storage/archive/warehousing, or any type of media or device suitable for storing instructions and/or data.

Stored on any one of the computer readable medium (media), the present invention includes software for controlling both the hardware of the general purpose/specialized computer or microprocessor, and for enabling the computer or microprocessor to interact with a human user or other mechanism utilizing the results of the present invention. Such software may include, but is not limited to, device drivers, operating systems, and user applications. Ultimately, such computer readable media further includes software for performing the present invention, as described above.

Included in the programming (software) of the general/specialized computer or microprocessor are software modules for implementing the teachings of the present invention, including, but not limited to, identifying plug-in devices, requesting registration file downloads, launching registration processes, and transferring registration data to service providers, according to processes of the present invention.

In the foregoing specification, the invention has been described with reference to specific embodiments thereof. It will, however, be evident that various modifications and

changes may be made thereto without departing from the broader spirit and scope of the invention. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

RECEIVED